



Chassis: Ashok Leyland/TATA/MAN or any similar chassis with or without cabin.

Superstructure: MS/SS pressed sections, square pipes, angles etc.

Pump Type: Single or double stage centrifugal type rear mounted.

Pump Capacity: L.P- 1800/2250/3000/4500/6000 LPM at 7-8.5 kg/cm² at suction lift of 3 meters.
H.P- 200/400 LPM at 20-40 kg/cm²

Power Take off: P.T.O of suitable ratio and torque to suit different engines.

Monitor: One monitor with suitable branch is provided on the top of the foam tender, which can rotate 360° in horizontal plane and 45° in vertical plane, however guided by dimensions of the body.

Water Tank: Upto 4000 liters capacity made from 3-5mm thick MS/SS plates.

Foam Tank: Upto 1000 liters capacity made from 3-5mm thick SS plates.

DCP System: Maximum 1000 kg capacity

Lockers: Lockers on both sides of the body with lids suitably hinged and closing device with quick release couplings, brackets, clamps are provided. Aluminum roller shutter/door on either side for storage of equipment is provided.

Accessories: As per client requirements

Standard: Conforming to IS: 10460

Kooverji Devshi & Co. Pvt. Ltd.

D 113, M.I.D.C. Industrial Area, Behind London Pilsner, Nerul, Navi Mumbai 400706

Registered Office: 7A Jeevan Asha, 60A Pedder Road, Mumbai 400026

Tel.: +91 22 27680487 / 88 Fax: +91 22 27621564

Email: contact@kooverjidevshi.com Web: www.kooverjidevshi.com