



Chassis: TATA or any similar chassis with or without cabin.

Superstructure: MS/SS pressed sections, square pipes, angles etc.

Pump Type: Single or double stage centrifugal type rear mounted.

Pump Capacity: 1800 LPM at 7 kg/cm² at suction lift of 3 meters.

Primer Type: Watering/ Exhaust ejector type capable of lifting water at the rate of 30cm/sec from 7 meters.

Power Take off: Small make P.T.O of suitable ratio and torque to suit different engines.

Water Tank: 1600-3000 liters capacity, made from 3-5mm thick MS/SS plates.

Monitor: One monitor with suitable branch pipe capable of producing 1100 LPM , is provided on the top of the tender, which can rotate 360° in horizontal plane and 45° in vertical plane, however guided by dimensions of the body.

Lockers: Lockers on both sides of the body with lids suitably hinged and closing device with quick release couplings, brackets, clamps are provided. Aluminum roller shutter/door on either side for storage of equipment is provided.

Accessories Revolving light, P.A system with 2 tone hooter, Fire bell/siren, reversing light, trafficator light, search light, breathing apparatus sets etc.

Kooverji Devshi & Co. Pvt. Ltd.

D 113, M.I.D.C. Industrial Area, Behind London Pilsner, Nerul, Navi Mumbai 400706

Registered Office: 7A Jeevan Asha, 60A Pedder Road, Mumbai 400026

Tel.: +91 22 27680487 / 88 Fax: +91 22 27621564

Email: contact@kooverjidevshi.com Web: www.kooverjidevshi.com